



EVQC & EVFC Electric Vehicle Chargers 30 to 180 kW EV Fast Chargers

Description

Power Innovations International's family of DC Fast Chargers are available in power ratings from 30 kW up to 180 kW in compact, all-in-one systems. Each charger offers highly flexible and field configurable Vac input power configurations with no de-rating.

This flexibility provides the ability to accept the most common distribution voltages in the same product, helping to reduce overall infrastructure costs and allow easier installation.

Key Features and Advantages

- Highly flexible power input with no de-rating
- Field replaceable power modules
- Greater than 1 million hours MTBF on PSU topology
- Multiple payment/authorization methods
 - RFID, credit card
- Remote upgrades via Over-the-Air updates
- Suitable for a broad range of EV use cases



Electrical Specifications

Model	Power Rating	Input Voltage	Output Voltage
EVQC030-M to EVQC060-M	30 to 60 kW	240 Vac Single Phase* 208 or 240 Vac Delta 480 Wye *up to 60 kW	250 to 920 Vdc
EVQC030	30 kW		
EVQC060	60 kW		
EVFC120	120 kW		
EVFC150	150 kW		
EVFC180	180 kW		

Mechanical and Environmental Specifications

Model	Mounting	Connectors	Standard Cable Length	Operating Temperature
EVQC030-M to EVQC060-M	Mobile / On Wheels	(1) CCS1, rated up to 60 kW	5 m	-30 °C to +50 °C
EVQC030	Pedestal or Wall Mount	(1) CCS1	5 m	
EVQC060	Pedestal	(1) CCS1	5 m	
EVFC120	All-in-One Cabinet	Up to (2) CCS1	4.5 m* or 5.5 m**	
EVFC150	All-in-One Cabinet	(1) CCS1	4.5 m* or 5.5 m**	
EVFC180	All-in-One Cabinet	Up to (2) CCS2	4.5 m* or 5.5 m**	

*with no cable management

**with cable management

Networking & Communication

Charging/Data Protocols	DIN 70121 and OCPP 1.6J compliant
Network Interface	Cellular 4G LTE, Wi-Fi
RFID	ISO/IEC 14443 A/B, ISO 15393, NFC Reader Mode

Document No.: GUIDE101
Last Updated: October 7, 2024
Supersedes: February 28, 2024

Power Innovations International
 1305 South 630 East
 American Fork, UT 84003
 United States
www.PowerInnovations.com



LITEON GROUP