

LITEON GROUP

## Description

Power Innovations International's (Pii) 3.3 kVA power supply unit (PSU) is a rectifier that converts AC or DC input power to 400 Vdc bus or 800 Vdc bus. The rectifier module can be used to charge batteries or to provide a stable, high voltage bus for other downstream power conversion, such as inverters or DC/DC converters. Multiple PSUs can be arranged to operate in parallel, and this rectifier module supports Modbus RS-485 communication.

## Features and Benefits

- 3.3 kVA PSU, with 0.8 to 1.0 power factor
- Single-phase AC input or DC input
  - **AC:** 120, 208, 240 or 277 V nominal
  - **DC:** 250 to 420 V
- Two configurable output voltages: 400 V or 800 V nominal
- Output voltage droop for current sharing between PSUs in large power systems (up to 200 kW)
- 95% efficiency at rated power (97% peak)
- Parallelable in power shelves (Pii part number: PF-1103-P20N)
- Constant power and constant current protection
- Modbus RS-485 communication protocol



## Specifications


Electrical	
Input Voltage	<b>AC:</b> 120, 208 to 277 V nominal (120 Vac to 305 Vac operating range) <b>DC:</b> 250 V to 420 V range
Input Frequency	50 / 60 Hz, DC; auto-sensing
Input Power Factor at Full Load	>0.99
Input Current	16.5 A max
Output Power	3.3 kVA
Output Voltage	250 Vdc to 920 Vdc full range; 400 & 800 Vdc nominal <b>400 V range:</b> adjustable 250 Vdc to 450 Vdc <b>800 V range:</b> adjustable 450 Vdc to 920 Vdc
Output Current	8.7 A maximum at 400 Vdc range 4.3 A maximum at 800 Vdc range
Efficiency	>95% at full load
Current Share Method	Droop
Communication Protocol	Modbus RS-485
Auxiliary Standby Supply	12 V / 0.2 A
Mechanical	
Dimensions (W x H x D)	5.18" x 1.57" x 12.71" (131.5 mm x 40 mm x 322.8 mm)
Cooling	Forced air cooling
Weight	5.5 lbs (2.5 kg)

LITEON GROUP

**Specifications (continued)**


Environmental	
Operating Temperature	-40 °C to +55 °C at full load; de-rated from +55 °C to +85 °C
Storage Temperature	-40 °C to +85 °C
Humidity	10% to 90% relative (non-condensing)
Altitude	Operating: 0 m to 3000 m Storage: 0 m to 15000 m
EMI	CISPR 22 Class A -6dB
Configurations	
PS-2332-EVC1-LF	<b>Tab color:</b> Green <b>Airflow direction:</b> Front-to-back airflow
PS-2332-EVC2-LF	<b>Tab color:</b> Blue <b>Airflow direction:</b> Back-to-front airflow
General	
Safety Standards	UL 2202 (AC & DC input); CE marking

**Product Dimensions (mm)**



LITEON GROUP

## Front Panel



1	“POWER” LED	Output power indicator: green-colored LED
2	“FAULT” LED	PSU fault indicator: amber-colored LED
3	Fans	Cooling fans

## Front Panel LED Status

Status	LED Green: Power	LED Amber: FAULT
Output Normal	<b>Solid Green</b>	Off
Storage Temperature	<b>Blinking Green @ 2 Hz</b>	Off
Output Disable/Fault	Off	<b>Solid Amber</b>
Output Disable/Firmware Update	Off	<b>Blinking Amber @ 2 Hz</b>

**Life Support Policy:** Power Innovations International (Pii) does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Pii reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Pii also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Document No.:** DATA118  
**Last Updated:** February 24, 2025

**Power Innovations International**  
1305 South 630 East  
American Fork, UT 84003  
United States  
[www.PowerInnovations.com](http://www.PowerInnovations.com)